




## Gemini


Gemini CCT Surface/Suspended Linear 1500mm Code: AGELED5/DD1/M3

Category	Commercial Linear Ancillary, Retail		
Application			
Specification	Performance		









- High specification fully enclosed linear luminaire suitable for most commercial and educational applications
- Microprism diffuser for enhanced photometric performance
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- · Powered by Philips

•	Pu	sh	pir	n re	elease	des	sign feature ensures a quick and easy installation

- Robust steel construction
- Suitable for surface and suspension

GENER/	AL INFORMATION
Wattage	40W
Lumens Delivered	3300lm - 5300lm (4000K)
Lm/W	131lm/W (4000K)
Beam Angle	70
CRI	80
ССТ	3000/4000K
Input	220-240V
Operating Temp	0°C - 50°C
SDCM	3
UGR	18
Product Weight without Packaging	6 kg

TECHNICAL INFORMATION				
Light Source	LED			
Colour / Finish	White			
IP Rating	IP20			
Class Protection	1			
Internal / External	Internal			
Surface / Recessed / Suspended	Ceiling, Suspended			
Lumen Depreciation	L70 54,000h			
Warranty (Years)	5			
CE Mark	Yes			
Height	55 mm			