












Gemini

Category	Commercial Linear	
Application	Ancillary, Retail	
Specification	Performance	

Gemini CCT Surface/Suspended Linear 1500mm Code: AGELED5/DD4









PRODUCT FEATURES

- $\bullet \ \ \text{High specification fully enclosed linear luminaire suitable for most commercial and}$ educational applications
- Microprism diffuser for enhanced photometric performance
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 $\,$ outputs, in one luminaire
- · Powered by Philips

www.ansell-lighting.com

- Push pin release design feature ensures a quick and easy installation
- · Robust steel construction
- Suitable for surface and suspension

GENERAL INFORMATION		
Wattage	40W	
Lumens Delivered	3300lm - 5300lm (4000K)	
Lm/W	131lm/W (4000K)	
Beam Angle	70	
CRI	80	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	-20°C - 50°C	
SDCM	3	
UGR	18	
Product Weight without Packaging	5.643 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	1	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	55 mm	

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750