



Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance

Guardian DALI

Guardian DALI Bulkhead Code: AGLED/3M/DA







PRODUCT FEATURES

- Ultra-slim profile LED polycarbonate bulkhead
- · Supplied with self-adhesive legend
- Choice of 1 or 3-hour emergency durations and features an intelligent charge system with temperature protection for enhanced safety and reliability
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- · Selectable self-test or manual test emergency operation for installation flexibility
- DALI2 addressable with Self-Test functionality, easily upgradable to OCTO Insight for smart lighting integration, and defaults to self-test mode when not connected to a DALI bus.
- 20mm side, end and rear cable entries
- Quick release LED array/gear tray assembly provides the installer the means to faster installation/maintenance

GENERAL INFORMATION		
Wattage	4W	
Lumens Delivered	145lm (Emergency)	
Lm/W	N/A	
Beam Angle	130	
CRI	80	
CCT	6500K	
Input	220/240V	
Operating Temp	0°C - 45°C	
SDCM	6	

TECHNICAL INFORMATION				
Light Source	LED			
Colour / Finish	White			
IP Rating	IP66			
IK Rating	IKO8			
Class Protection	2			
Internal / External	Internal / External			
Surface / Recessed / Suspended	Surface			
Lumen Depreciation	L70 60,000h			
Warranty (Years)	7			
CE Mark	Yes			
Height	55 mm			











Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance

Guardian DALI

Guardian DALI Bulkhead Code: AGLED/3M/DA





	ACCESSORIES	
ASBP/39	3.2V 3Ah Li-FePO4 Replacement Battery	

Belfast: +44 (0) 2890 773750

Warrington: +44 (0) 1942 433333



