Guardian

Part of the Emergency product category

Model	Guardian Bulkhead
Code	AGLED/3M
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	3W
Operating Temp	0°C - 40°C
Lumens Delivered	167lm (Emergency)
CCT	6500K
Beam Angle	130

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.48 kg
Colour / Finish	White

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Recessed, Wall
Power Factor	0.4
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- Ultra-slim profile LED polycarbonate bulkhead
- Selectable self-test or manual test emergency operation for installation flexibility
- Supplied with self-adhesive legend
- DALI2 addressable with Self-Test functionality, easily upgradable to OCTO Insight for smart lighting integration, and defaults to self-test mode when not connected to a DALI bus.
- Choice of 1 or 3-hour emergency durations and features an intelligent charge system with temperature protection for enhanced safety and reliability

ACCESSORIES

AGLED/KIT	Guardian Bulkhead Semi-Recessing Kit White

ICEL CERTIFIED
ICEL 001 - 050





Guardian

Part of the Emergency product category

Model	Guardian Bulkhead
Code	AGLED/3M
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail











