



# Guardian

Part of the Emergency product category



<b>Model</b>	Guardian Bulkhead
<b>Code</b>	AGLED/3M
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	3W
<b>Operating Temp</b>	0°C - 40°C
<b>Lumens Delivered</b>	167lm (Emergency)
<b>CCT</b>	6500K
<b>Beam Angle</b>	130

## MATERIAL INFORMATION

<b>Main Material</b>	Polycarbonate
<b>Diffuser Material</b>	Polycarbonate
<b>Product Weight without</b>	0.48 kg
<b>Packaging</b>	
<b>Colour / Finish</b>	White

## TECHNICAL INFORMATION

<b>Class Protection</b>	2
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	6
<b>CRI</b>	80
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Ceiling, Recessed, Wall
<b>Power Factor</b>	0.4
<b>L70 @ 25°C</b>	L70 B50 60,000h

## PRODUCT FEATURES

- Ultra-slim profile LED polycarbonate bulkhead
- Selectable self-test or manual test emergency operation for installation flexibility
- Supplied with self-adhesive legend
- DALI2 addressable with Self-Test functionality, easily upgradable to OCTO Insight for smart lighting integration, and defaults to self-test mode when not connected to a DALI bus.
- Choice of 1 or 3-hour emergency durations and features an intelligent charge system with temperature protection for enhanced safety and reliability

## ACCESSORIES

AGLED/KIT	Guardian Bulkhead Semi-Recessing Kit White
-----------	--





# Guardian



Part of the Emergency product category

<b>Model</b>	Guardian Bulkhead
<b>Code</b>	AGLED/3M
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

