




Guardian

Guardian Bulkhead Code: AGLED/3M








Category

Application

Specification

Emergency

Performance



Ancillary, Commercial, Education, Healthcare,

Hospitality, Industrial, Retail

- Ultra-slim profile LED polycarbonate bulkhead
- · Self-test as standard
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- Viewing distance 18 metres

- Supplied with self-adhesive legend
- 20mm side, end and rear cable entries
- Quick release LED array/gear tray assembly provides the installer the means to faster installation/maintenance

| GENERAL INFORMATION | | |
|----------------------------------|-------------------|--|
| Wattage | 3W | |
| Lumens Delivered | 167Im (Emergency) | |
| Beam Angle | 130 | |
| CRI | 80 | |
| ССТ | 6500K | |
| Input | 220-240V | |
| Operating Temp | 0°C - 40°C | |
| SDCM | 6 | |
| Product Weight without Packaging | 0.48 kg | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------------------|--|
| Light Source | LED | |
| Colour / Finish | White | |
| IP Rating | IP66 | |
| Class Protection | 2 | |
| Internal / External | Internal / External | |
| Surface / Recessed / Suspended | Ceiling, Recessed, Wall | |
| Lumen Depreciation | L70 60,000h | |
| Warranty (Years) | 7 | |
| CE Mark | Yes | |
| Accessories | AGLED/KIT | |
| | | |

