



Halo



Part of the High/Low Bay product category

Model Halo Highbay 1 Emergency Black
Code AHALO1/BL/1/M3
Application Commercial, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	10W/25W
Operating Temp	-20°C - 40°C
Lumens Delivered	1200lm - 3000lm (4000K)
lm/W	110lm/W
CCT	3000K/4000K
UGR	32
Beam Angle	100

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Colour / Finish	Black
Diameter	331 mm
Height	418 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Suspended
Power Factor	0.9
L70 @ 25°C	L70 54,000h

PRODUCT FEATURES

- Modern decorative low/high bay with a unique Halo ring design, suitable for retail, commercial, educational, and healthcare applications
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Unique halo ring design with black and white finishes provide an aesthetic and modern appearance, suited for many architectural applications
- Push-fit terminals for quick and efficient installation, with direct wiring into the fitting.
- Emergency variant

ACCESSORIES

AHALO1/REFBL/1	Halo Highbay 1 Reflector Accessory Black
AHALO1/REFWH/1	Halo Highbay 1 Reflector Accessory White





Halo



Part of the High/Low Bay product category



Model Halo Highbay 1 Emergency Black
Code AHALO1/BL/1/M3
Application Commercial, Industrial, Retail

