Helder

Part of the Bulkheads product category

Model	Helder CCT Oval Bulkhead Black
Code	AHELED/OB
Application	Ancillary, Hospitality, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	12.5W
Operating Temp	-5°C - 25°C
Lumens Delivered	1100lm (4000K)
lm/W	96lm/W (4000K)
CCT	3000/4000/6500K
Beam Angle	110

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.289 kg
Colour / Finish	Black

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Ceiling, Wall
Power Factor	0.5
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- All polycarbonate oval bulkhead suitable for external semi-commercial and residential applications
- Fast loop-in / loop-out connections
- CCT selectable between 3000K, 4000K and 6500K
- Body options of black or white
- Polycarbonate opal diffuser





Helder

Part of the Bulkheads product category

Model	Helder CCT Oval Bulkhead Black
Code	AHELED/OB
Application	Ancillary, Hospitality, Outdoor, Residential, Retail









