Helix

5YR IP66 IK08 Dimmable

Part of the Streetlights product category

Model	Helix Post Top
Code	AHPT/1
Application	Commercial, Education, Healthcare, Hospitality, Outdoor, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	20W - 75W
Operating Temp	-30°C to 50°C
Lumens Delivered	2500lm - 8800lm (4000K)
lm/W	118lm/W
CCT	3000K/4000K selectable
Beam Angle	145

MATERIAL INFORMATION

Main Material	Aluminum + PC lens + Tempered Glass
Diffuser Material	PC lens + Tempered Glass
Product Weight without Packaging	8.04 kg
Colour / Finish	Black
Diameter	450 mm
Height	526 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	4
CRI	70
Internal / External	External
Power Factor	0.9
L70 @ 25°C	L80 60,000h

PRODUCT FEATURES

- Modern die-cast aluminium post top lantern Ideal for large carparks and large open areas
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 4 outputs, in one luminaire
- Electrostatic paint finish for enhanced corrosion resistance
- Advanced lens technology providing optimum performance and control
- Suitable for residential and commercial use

ACCESSORIES

AHPT/1/60SBA	Helix Post Top 60mm Spigot Bracket Accessory





Helix

Part of the Streetlights product category

Model	Helix Post Top
Code	AHPT/1
Application	Commercial, Education, Healthcare, Hospitality, Outdoor, Retail





