

@ansell_lighting f ansellighting Image: Ansell Lighting Image: Construction of the sellighting

Helix

Helix CCT Post Top 2 DALI Code: AHPTLED/2/DD3





Category	Streetlights
Application	Commercial, Education, Healthcare, Hospitality,
	Outdoor, Retail
Specification	Architectural

PRODUCT FEATURES

- Modern die-cast aluminium post top lantern Ideal for large carparks and large open areas
- Electrostatic paint finish for enhanced corrosion resistance
- Suitable for residential and commercial use

- CCT selectable between 3000K and 4000K
- · Advanced lens technology providing optimum performance and control.
- 76mm spigot bracket

GENERAL INFORMATION		
Wattage	75W	
Lumens Delivered	8500lm (4000K)	
Lm/W	114lm/W (4000K)	
Beam Angle	145	
CRI	70	
CCT	3000/4000K	
Input	220/240V	
Operating Temp	-30°C - 50°C	
SDCM	4	

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Black		
IP Rating	IP66		
Class Protection	1		
Internal / External	External		
Surface / Recessed / Suspended	Pole		
Lumen Depreciation	L80 100,000h		
Warranty (Years)	5		
CE Mark	Yes		
Diameter	450 mm		
Height	526 mm		

