












Juno


| Application | Commercial, Education, Retail | |
|---------------|-------------------------------|--|
| Specification | Architectural | |

Juno Recessed Modular 1-10V DALI-Emergency Code: AJUN/1/DD4/DM3









- Architectural LED recessed modular suitable for education, commercial and healthcare applications
- Dual direct / indirect output. Direct from the centre micro-prism line coupled with indirect output from the side diffuser sections. Providing a perfect combination for task and ambient lighting from one source.
- Power and CCT selectable; offering a choice of 4 outputs and 3 colour temperature options, in one luminaire
- TPa as standard

- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Black micro reflector and micro-prism diffuser ensure reduced glare and visual comfort
- OCTO compatible tunable white version available with CCT selection between 2700K-5000K ideal for any Human Centric Lighting requirements

| GENERAL INFORMATION | | |
|---------------------|---------------------------------------|--|
| Wattage | 36W | |
| Lumens Delivered | 2500lm - 4400lm (4000K) | |
| Lm/W | 125lm/W (4000K) | |
| Beam Angle | 70 | |
| CRI | 80 | |
| CCT | 3000K/4000K/6500K | |
| Input | 220-240V | |
| Operating Temp | 0°C - 45°C | |
| SDCM | 3 | |
| UGR | 18 | |
| Cut-Out Size | 570*570mm | |
| | · · · · · · · · · · · · · · · · · · · | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------|--|
| Light Source | LED | |
| Colour / Finish | White | |
| IP Rating | IP40 | |
| Class Protection | 2 | |
| Internal / External | Internal | |
| Surface / Recessed / Suspended | Recessed | |
| Lumen Depreciation | L70 54,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

