

Commercial, Education, Retail


Architectural

Juno

Juno Recessed Modular DALI-Emergency Code: AJUN/1/DM3




-	-	



Application

Specification



- Architectural LED recessed modular suitable for education, commercial and healthcare
 applications
- Dual direct / indirect output. Direct from the centre micro-prism line coupled with indirect output from the side diffuser sections. Providing a perfect combination for task and ambient lighting from one source.
- Power and CCT selectable; offering a choice of 4 outputs and 3 colour temperature options, in one luminaire
- TPa as standard

GENERAL INFORMATION		
Wattage	20W - 36W	
Lumens Delivered	2500lm - 4400lm (4000K)	
Lm/W	125lm/W (4000K)	
Beam Angle	70	
CRI	80	
ССТ	3000K/4000K/6500K	
Input	220-240V	
Operating Temp	0°C - 45°C	
SDCM	3	
UGR	18	
Cut-Out Size	570*570mm	
Product Weight without Packaging	3.572 kg	

- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Black micro reflector and micro-prism diffuser ensure reduced glare and visual comfort
- OCTO compatible tunable white version available with CCT selection between 2700K-5000K ideal for any Human Centric Lighting requirements

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	White		
IP Rating	IP40		
Class Protection	2		
Internal / External	Internal		
Surface / Recessed / Suspended	Recessed		
Lumen Depreciation	L70 54,000h		
Warranty (Years)	5		
CE Mark	Yes		

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750