













## Juno

## Juno Recessed Modular OCTO Smart Control Code: AJUNLED/OCTO







## **PRODUCT FEATURES**

- Architectural LED recessed modular suitable for education, commercial and healthcare applications
- Dual direct / indirect output. Direct from the centre micro-prism centre line coupled with indirect output from the side diffuser sections. Providing a perfect combination for task and ambient lighting from one source
- Micro-prism diffuser design ensures reduced glare and visual comfort
- · Powered by Tridonic

- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Black polycarbonate micro reflector low glare design
- OCTO compatible tunable white version available with CCT selection between 2700K-5000K ideal for any Human Centric Lighting requirements
- TPa as standard

GENERAL INFORMATION		
Wattage	34W	
Lumens Delivered	4400lm	
Lm/W	131lm/W	
Beam Angle	65	
CRI	80	
CCT	4000K	
Input	220/240V	
Operating Temp	-20°C - 40°C	
SDCM	4	
UGR	17	
Cut-Out Size	590x590mm	
Product Weight without Packaging	3.58 kg	

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP40
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 60,000h
Warranty (Years)	5
CE Mark	Yes
Height	50 mm

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

