

@ansell_lighting



ansellighting



Ansell Lighting





ansell_lighting

Juno

Juno Recessed Modular OCTO Smart Control
Code: AJUNLED/TW/OCTO

Category	Commercial Panels
Application	Commercial, Education, Healthcare
Specification	Architectural



- Architectural LED recessed modular suitable for education, commercial and healthcare applications
- Dual direct / indirect output. Direct from the centre micro-prism centre line coupled with indirect output from the side diffuser sections. Providing a perfect combination for task and ambient lighting from one source
- Micro-prism diffuser design ensures reduced glare and visual comfort
- Powered by Tridonic
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Black polycarbonate micro reflector low glare design
- OCTO compatible tunable white version available with CCT selection between 2700K-5000K ideal for any Human Centric Lighting requirements
- TPa as standard

GENERAL INFORMATION	
Wattage	37W
Lumens Delivered	3900lm - 4300lm (2700K - 6500K)
Lm/W	104lm/W - 116lm/W (2700K - 6500K)
Beam Angle	65
CRI	80
CCT	2700-5000K
Input	220-240V
Operating Temp	-20°C - 40°C
SDCM	3
UGR	17
Cut-Out Size	590x590mm
Product Weight without Packaging	3.63 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP40
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 60,000h
Warranty (Years)	5
CE Mark	Yes
Height	50 mm

