



Juno



Part of the Commercial Panels product category

Model	Juno Recessed Modular
Code	AJUNLED
Application	Commercial, Education, Healthcare

GENERAL INFORMATION

Input	220-240V
Wattage	34W
Operating Temp	-20°C - 40°C
Lumens Delivered	4400lm
lm/W	131lm/W
CCT	4000K
UGR	17
Beam Angle	70

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without Packaging	3.372 kg
Colour / Finish	White
Height	50 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.9
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- Architectural LED recessed modular suitable for education, commercial and healthcare applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Dual direct / indirect output. Direct from the centre micro-prism centre line coupled with indirect output from the side diffuser sections. Providing a perfect combination for task and ambient lighting from one source
- Black polycarbonate micro reflector low glare design
- Micro-prism diffuser design ensures reduced glare and visual comfort





Juno



Part of the Commercial Panels product category

Model Juno Recessed Modular
Code AJUNLED
Application Commercial, Education, Healthcare

