Kala

5YR IP20 Dimmable ON-SITE WARRANTY 2 YEARS

Part of the Pendants product category

Model	Kala Round Panel 600mm 3CCT TP(a) (driverless)
Code	AKAL2/1
Application	Ancillary, Commercial, Education, Hospitality, Retail

GENERAL INFORMATION

Input	33-38V
Wattage	40W
Operating Temp	-10°C - 45°C
Lumens Delivered	4800lm (4000K)
lm/W	120lm/W
CCT	3000K/4000K/6500K
UGR	28
Beam Angle	110

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polystyrene
Product Weight without Packaging	2.51 kg
Colour / Finish	White
Diameter	600 mm
Height	14 mm

TECHNICAL INFORMATION

Class Protection	3
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling, Recessed, Suspended
Power Factor	0.9
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- Architectural circular LED pendant with die-cast housing suitable for residential, hospitality and commercial applications
- CCT selectable between 3000K, 4000K and 6500K
- Intelligent 2 part construction separates pendant head from suspension, surface and recessing mounting kit accessories (sold separately) ensuring maximum versatility for a diverse range of installation applications
- Suspension kit includes ceiling rose, ensuring a quick and easy installation
- TPa diffuser as standard

ACCESSORIES

AKSR2/1	Kala 600mm Surface and Recessed Kit (with driver)
AKSK2/1	Kala 600mm Suspension Kit (with driver)

ACCESSORIES

AKSR2/1	Kala 600mm Surface and Recessed Kit (with driver)
AKSK2/1	Kala 600mm Suspension Kit (with driver)





Kala

Part of the Pendants product category

Model	Kala Round Panel 600mm 3CCT TP(a) (driverless)
Code	AKAL2/1
Application	Ancillary, Commercial, Education, Hospitality, Retail













