



Category	Pendants
Application	Ancillary, Commercial, Education, Hospitality, Retail
Specification	Architectural

## Kala

Kala Round Panel 600mm 3CCT TP(a) (driverless) Code: AKAL2/1







## **PRODUCT FEATURES**

- · Architectural circular LED pendant with die-cast housing suitable for residential, hospitality and commercial applications
- Intelligent 2 part construction separates pendant head from suspension, surface and recessing mounting kit accessories (sold separately) ensuring maximum versatility for a diverse range of installation applications
- TPa diffuser as standard
- · Please note a suspension kit accessory or surface and recessing kit accessory are required for installation

	GENERAL INFORMATION
Wattage	40W
Lumens Delivered	4800lm (4000K)
Lm/W	120lm/W
Beam Angle	110
CRI	80
ССТ	3000/4000/6500K
Input	33-38V
Operating Temp	-10°C - 45°C
SDCM	6
UGR	28
Cut-Out Size	200-220mm
Product Weight without Packagi	ing 2.51 kg

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	3	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Recessed, Suspended	
Lumen Depreciation	L80 100,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	600 mm	
Height	14 mm	





Belfast: +44 (0) 2890 773750 Warrington: +44 (0) 1942 433333



f ansellighting ansell\_lighting



Triac dimmable as standard

• Suspension kit includes ceiling rose, ensuring a quick and easy installation

• CCT selectable between 3000K, 4000K and 6500K







Category	Pendants
Application	Ancillary, Commercial, Education, Hospitality, Retail
Specification	Architectural

## Kala

Kala Round Panel 600mm 3CCT TP(a) (driverless) Code: AKAL2/1





ACCESSORIES		
AKSR2/1	Kala 600mm Surface and Recessed Kit (with driver)	
AKSK2/1	Kala 600mm Suspension Kit (with driver)	
	MANDATORY ACCESSORIES	
AKSR2/1	Kala 600mm Surface and Recessed Kit (with driver)	
AKSK2/1	Kala 600mm Suspension Kit (with driver)	



