

Kamar

Kamar Floodlight 1 Tunable White 8° Symmetrical **Code:** AKAR1/1/TW/NB/OCTO



219.5

- High performance projector with a vast number of customisation options suitable for all commercial, hospitality, retail and industrial applications
- + Beam angle options ranging from 8° up to 60° ensure suitability for most applications
- Low glare hood and honeycomb film accessories available for projects when glare
 optimisation and upward lighting are considerations
- Die-cast contruction provides sleek and modern appearance, perfect for architectural applications
- Multiple control options available, DALI, DMX and Casambi (35W and 100W only) as well as an extensive collection of CCT options provide complete control and light output for even the most complex of projects

GENERAL INFORMATION		
Wattage	35W	
Lumens Delivered	2300lm	
Lm/W	65lm/W	
Beam Angle	8°	
CRI	80	
CCT	2200-4000K	
Input	220-240V	
Operating Temp	-30°C - 50°C	
SDCM	6	
Product Weight without Packaging	3.91 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Silver	
IP Rating	IP66	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Floor, Wall	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	220 mm	
Height	330 mm	



Category	Floodlights
Application	Commercial, Hospitality, Industrial, Outdoor, Retail
Specification	Performance

