

Kamar

Kamar Floodlight 1 Tunable White 60° Code: AKAR1/1/TW/UWB/OCTO






- High performance projector with a vast number of customisation options suitable for all commercial, hospitality, retail and industrial applications
- Beam angle options ranging from 8° up to 60° ensure suitability for most applications
- Low glare hood and honeycomb film accessories available for projects when glare
 optimisation and upward lighting are considerations

@ansell_lighting	f anselllighting
Ansell Lighting	ansell_lighting

Category	Floodlights
Application	Commercial, Hospitality, Industrial, Outdoor, Retail
Specification	Performance



- Die-cast contruction provides sleek and modern appearance, perfect for architectural applications
- Multiple control options available, DALI, DMX and Casambi (35W and 100W only) as well as an extensive collection of CCT options provide complete control and light output for even the most complex of projects

GENERAL INFORMATION		
Wattage	35W	
Lumens Delivered	3800lm	
Lm/W	105lm/W	
Beam Angle	60°	
CRI	80	
ССТ	2200-4000K	
Input	220-240V	
Operating Temp	-30°C - 50°C	
SDCM	6	
Product Weight without Packaging	3.91 kg	

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Silver		
IP Rating	IP66		
Class Protection	1		
Internal / External	Internal / External		
Surface / Recessed / Suspended	Floor, Wall		
Lumen Depreciation	L70 54,000h		
Warranty (Years)	5		
CE Mark	Yes		
Diameter	220 mm		
Height	330 mm		

