


Kamar

Kamar Floodlight 1 Tunable White 30° Code: AKAR1/1/TW/WB/OCTO






- commercial, hospitality, retail and industrial applications • Beam angle options ranging from 8° up to 60° ensure suitability for most applications
- Low glare hood and honeycomb film accessories available for projects when glare optimisation and upward lighting are considerations

| | Sell H T I N G |
|--------------------|-------------------|
| @ansell_lighting | f ansellighting |
| in Ansell Lighting | ansell_lighting |

| Category | Floodlights |
|---------------|------------------------------------------------------|
| Application | Commercial, Hospitality, Industrial, Outdoor, Retail |
| Specification | Performance |



- Die-cast contruction provides sleek and modern appearance, perfect for architectural applications
- Multiple control options available, DALI, DMX and Casambi (35W and 100W only) as well as an extensive collection of CCT options provide complete control and light output for even the most complex of projects

| GENERAL INFORMATION | | |
|---------------------|------------------------------------------------------------------------------|--|
| 35W | | |
| 4000lm | | |
| 110lm/W | | |
| 30° | | |
| 80 | | |
| 2200-4000K | | |
| 220-240V | | |
| -30°C - 50°C | | |
| 6 | | |
| 3.91 kg | | |
| | 35W 4000lm 110lm/W 30° 80 2200-4000К 220-240V -30°C - 50°C 6 | |

| TECHNICAL INFORMATION | | |
|--------------------------------|---------------------|--|
| Light Source | LED | |
| Colour / Finish | Silver | |
| IP Rating | IP66 | |
| Class Protection | 1 | |
| Internal / External | Internal / External | |
| Surface / Recessed / Suspended | Floor, Wall | |
| Lumen Depreciation | L70 54,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Diameter | 220 mm | |
| Height | 330 mm | |

