


Kamar

Kamar Floodlight 3 RGBW 3000K 20° x 60° Code: AKAR3/1/RGBW30/ASY/OCTO





Category

Application

Specification

- · High performance projector with a vast number of customisation options suitable for all commercial, hospitality, retail and industrial applications
- Beam angle options ranging from 8° up to 60° ensure suitability for most applications
- · Low glare hood and honeycomb film accessories available for projects when glare optimisation and upward lighting are considerations

•	Die-cast contruction provides sleek and modern appearance, perfect for architectural
	applications

• Multiple control options available, DALI, DMX and Casambi (35W and 100W only) as well as an extensive collection of CCT options provide complete control and light output for even the most complex of projects

Floodlights

Performance

GENERAL INFORMATION				
Wattage	100W			
Beam Angle	20/60°			
CRI	80			
CCT	RGBW (RGB+3000K)			
Input	220-240V			
Operating Temp	-30°C - 50°C			
SDCM	6			
Product Weight without Packaging	10.15 kg			

TECHNICAL INFORMATION				
Light Source	LED			
Colour / Finish	Silver			
IP Rating	IP66			
Class Protection	1			
Internal / External	Internal / External			
Surface / Recessed / Suspended	Floor, Pole, Wall			
Lumen Depreciation	L70 54,000h			
Warranty (Years)	5			
CE Mark	Yes			
Diameter	394 mm			
Height	452 mm			



Commercial, Hospitality, Industrial, Outdoor, Retail

452	•	

