





Floodlights

Performance

@ansell_lighting



Commercial, Hospitality, Industrial, Outdoor, Retail




in Ansell Lighting



Kamar

Kamar Floodlight 3 RGBW 3000K 30° Symmetrical Code: AKAR3/1/RGBW30/WB/DMX





Category

Application

Specification

- High performance projector with a vast number of customisation options suitable for all commercial, hospitality, retail and industrial applications
- Beam angle options ranging from 8° up to 60° ensure suitability for most applications
- · Low glare hood and honeycomb film accessories available for projects when glare optimisation and upward lighting are considerations
- Die-cast contruction provides sleek and modern appearance, perfect for architectural applications
- Multiple control options available, DALI, DMX and Casambi (35W and 100W only) as well as an extensive collection of CCT options provide complete control and light output for even the most complex of projects

GENERAL INFORMATION		
Wattage	100W	
Beam Angle	30°	
CRI	80	
CCT	RGBW (RGB+3000K)	
Input	220-240V	
Operating Temp	-30°C - 50°C	
SDCM	6	
Product Weight without Packaging	10.39 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Silver	
IP Rating	IP66	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Floor, Pole, Wall	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	394 mm	
Height	452 mm	



www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750