



Commercial, Hospitality, Industrial, Outdoor, Retail









Kamar

Kamar Floodlight 4 2200K 20° x 60° Asymmetrical Code: AKAR4/1/22/ASY/DD3





Floodlights

Architectural

Category

Application

Specification

- High performance projector with a vast number of customisation options suitable for all commercial, hospitality, retail and industrial applications
- Beam angle options ranging from 8° up to 60° ensure suitability for most applications
- Low glare hood and honeycomb film accessories available for projects when glare optimisation and upward lighting are considerations
- Die-cast contruction provides sleek and modern appearance, perfect for architectural applications
- Multiple control options available, DALI, DMX and Casambi (35W and 100W only) as well
 as an extensive collection of CCT options provide complete control and light output for
 even the most complex of projects

GENERAL INFORMATION		
Wattage	150W	
Lumens Delivered	12750lm	
Lm/W	85lm/W	
Beam Angle	20/60°	
CRI	80	
CCT	2200K	
Input	220-240V	
Operating Temp	-30°C - 50°C	
SDCM	6	
Product Weight without Packaging	10.39 kg	

TECHNICAL INFORMATION		
LED		
Silver		
IP66		
1		
Internal / External		
Floor, Pole, Wall		
L70 54,000h		
5		
Yes		
394 mm		
452 mm		
	LED Silver IP66 1 Internal / External Floor, Pole, Wall L70 54,000h 5 Yes 394 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

