












Kamar

Kamar Floodlight 4 3000K 30° Symmetrical DALI Code: AKAR4/1/30/WB/DD3







- High performance projector with a vast number of customisation options suitable for all commercial, hospitality, retail and industrial applications
- Beam angle options ranging from 8° up to 60° ensure suitability for most applications
- Low glare hood and honeycomb film accessories available for projects when glare optimisation and upward lighting are considerations
- Die-cast contruction provides sleek and modern appearance, perfect for architectural applications
- Multiple control options available, DALI, DMX and Casambi (35W and 100W only) as well
 as an extensive collection of CCT options provide complete control and light output for
 even the most complex of projects

| GENERAL INFORMATION | | |
|----------------------------------|--------------|--|
| Wattage | 150W | |
| Lumens Delivered | 12750lm | |
| Lm/W | 85lm/W | |
| Beam Angle | 30° | |
| CRI | 80 | |
| CCT | 3000K | |
| Input | 220-240V | |
| Operating Temp | -30°C - 50°C | |
| SDCM | 6 | |
| Product Weight without Packaging | 10.39 kg | |
| | | |

| TECHNICAL INFORMATION | | |
|--------------------------------|---------------------|--|
| Light Source | LED | |
| Colour / Finish | Silver | |
| IP Rating | IP66 | |
| Class Protection | 1 | |
| Internal / External | Internal / External | |
| Surface / Recessed / Suspended | Floor, Pole, Wall | |
| Lumen Depreciation | L70 54,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Diameter | 394 mm | |
| Height | 452 mm | |

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

