


@ansell_lighting f ansell_lighting ansell_lighting

Commercial, Hospitality, Industrial, Outdoor, Retail

Kamar

Kamar Floodlight 4 4000K 20° x 60° Asymmetrical **Code:** AKAR4/1/40/ASY/DD3





Category

Application

Specification

- High performance projector with a vast number of customisation options suitable for all
 commercial, hospitality, retail and industrial applications
- Beam angle options ranging from 8° up to 60° ensure suitability for most applications
- Low glare hood and honeycomb film accessories available for projects when glare
 optimisation and upward lighting are considerations
- Die-cast contruction provides sleek and modern appearance, perfect for architectural applications
- Multiple control options available, DALI, DMX and Casambi (35W and 100W only) as well as an extensive collection of CCT options provide complete control and light output for even the most complex of projects

Floodlights

Architectural

| GENERAL INFORMATION | | |
|----------------------------------|--------------|--|
| Wattage | 150W | |
| Lumens Delivered | 12750lm | |
| Lm/W | 85lm/W | |
| Beam Angle | 20/60° | |
| CRI | 80 | |
| CCT | 4000K | |
| Input | 220-240V | |
| Operating Temp | -30°C - 50°C | |
| SDCM | 6 | |
| Product Weight without Packaging | 10.39 kg | |

| TECHNICAL INFORMATION | | | |
|--------------------------------|---------------------|--|--|
| Light Source | LED | | |
| Colour / Finish | Silver | | |
| IP Rating | IP66 | | |
| Class Protection | 1 | | |
| Internal / External | Internal / External | | |
| Surface / Recessed / Suspended | Floor, Pole, Wall | | |
| Lumen Depreciation | L70 54,000h | | |
| Warranty (Years) | 5 | | |
| CE Mark | Yes | | |
| Diameter | 394 mm | | |
| Height | 452 mm | | |

