Kestrel

Part of the Emergency product category

Model	Kestrel Exit Sign
Code	AKESLED/3M
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	2.3W
Operating Temp	0°C - 40°C
CCT	6500K

MATERIAL INFORMATION

Main Material	Polycarbonate
Product Weight without Packaging	0.63 kg
Colour / Finish	White
Height	174 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	Ra 60
Internal / External	Internal
Surface / Recessed / Suspended	Suspended
Power Factor	0.25
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Ultra slim suspended LED emergency exit sign
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- Supplied with all legend options - arrow down, arrow up and arrow left/right
- Selectable self-test/manual test emergency as standard





Kestrel

Part of the Emergency product category

Model	Kestrel Exit Sign
Code	AKESLED/3M
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail





