



# Kite



Part of the Emergency product category



**Model** Kite Emergency Bulkhead  
**Code** AKTLED/3M/ST  
**Application** Ancillary, Industrial

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	3W
<b>Operating Temp</b>	0°C - 40°C
<b>Lumens Delivered</b>	67lm (Emergency), 138lm (Standard)
<b>CCT</b>	6500K
<b>Beam Angle</b>	120

## MATERIAL INFORMATION

<b>Main Material</b>	Polycarbonate
<b>Diffuser Material</b>	Polycarbonate
<b>Product Weight without Packaging</b>	0.433 kg
<b>Colour / Finish</b>	White
<b>Height</b>	120 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	6
<b>CRI</b>	70
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Ceiling, Wall
<b>Power Factor</b>	0.34
<b>L70 @ 25°C</b>	L70 B50 50,000h

## PRODUCT FEATURES

- Modern ultra-slim profile IP65 LED polycarbonate bulkhead
- Self-test as standard
- Aesthetically designed for modern appearance
- Supplied with self-adhesive legend
- 20mm side and rear cable entries





# Kite



Part of the Emergency product category

**Model** Kite Emergency Bulkhead  
**Code** AKTLED/3M/ST  
**Application** Ancillary, Industrial

