Kite

Part of the Emergency product category

Model	Kite Emergency Bulkhead
Code	AKTLED/3M/ST
Application	Ancillary, Industrial



GENERAL INFORMATION

Input	220-240V
Wattage	3W
Operating Temp	0°C - 40°C
Lumens Delivered	67lm (Emergency), 138lm (Standard)
CCT	6500K
Beam Angle	120

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.433 kg
Colour / Finish	White
Height	120 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Power Factor	0.34
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Modern ultra-slim profile IP65 LED polycarbonate bulkhead
- Selectable self-test/manual test as standard
- Aesthetically designed for modern appearance
- Supplied with self-adhesive legend
- 20mm side and rear cable entries

Kite

Part of the Emergency product category

Model	Kite Emergency Bulkhead
Code	AKTLED/3M/ST
Application	Ancillary, Industrial



