



Kite Emergency Bulkhead Maintained / Non-Maintained White



- Modern ultra-slim profile IP65 LED polycarbonate bulkhead
- Self-test as standard
- Aesthetically designed for modern appearance
- Supplied with self-adhesive legend
- 20mm side and rear cable entries
- Hinged screwless gear tray for ease of installation
- Viewing distance 20 metres

Features

Feature 1	Modern ultra-slim profile IP65 LED polycarbonate bulkhead
Feature 2	Self-test as standard
Feature 3	Aesthetically designed for modern appearance
Feature 4	Supplied with self-adhesive legend
Feature 5	20mm side and rear cable entries
Feature 6	Hinged screwless gear tray for ease of installation
Feature 7	Viewing distance 20 metres



General Information

Lamp Type	LED
Emergency	Yes
Self Test	Yes
IP Rating	IP65
IK Rating	IK08
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Warranty (Years)	5
Material	Polycarbonate
Technical Information	
Wattage	3W
Lumens Delivered	67lm (Emergency), 138lm (Standard)
Beam Angle	120
CRI	70
CCT	6500K
Input	220/240V
Hertz	50/60Hz
Operating Temp	0°C - 40°C
Lumen Depreciation	L70 50,000h
Power Factor	0.34



