



@ansell_lighting



ansellighting



Ansell Lighting







ansell_lighting

Leo Bollard Connected by WIZ

OCTO Leo Bollard 1000mm Tunable White

Code: ALEOLED/100/GR/OCTOW

Category	Bollards
Application	Hospitality, Outdoor, Residential, Retail
Specification	Architectural



PRODUCT FEATURES

- Modern styled WIZ embedded bollard with polycarbonate construction suitable for residential and hospitality applications
- White reflector with clear polycarbonate diffuser
- Supplied c/w root mounting kit, can be surface mounted with rawbolts
- Please consider WiFi signal strength for this product
- Connects directly to your WiFi network using Bluetooth technology to support seamless pairing
- Polycarbonate construction is ideal for coastal applications
- Tunable between 2700K - 6500K via WIZ app and voice control

GENERAL INFORMATION

Wattage	11W
Lumens Delivered	840lm - 850lm (2700K - 6500K)
Lm/W	69lm/W - 77lm/W (2700K - 6500K)
Beam Angle	130
CRI	80
CCT	2700-6500K
Input	220/240V
Operating Temp	-10°C - 40°C
SDCM	6
Product Weight without Packaging	2.041 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Black
IP Rating	IP65
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Floor
Lumen Depreciation	L70 36,000h
Warranty (Years)	3
CE Mark	Yes
Diameter	180 mm
Height	1,000 mm

