





Bollards

Architectural

@ansell_lighting









ansell_lighting

eo Bollard Connected by

OCTO Leo Bollard 1000mm Tunable White Code: ALEOLED/100/GR/OCTOW








Category

Application

Specification



Hospitality, Outdoor, Residential, Retail

PRODUCT FEATURES

- Modern styled WiZ embedded bollard with polycarbonate construction suitable for residential and hospitality applications
- · White reflector with clear polycarbonate diffuser
- Supplied c/w root mounting kit, can be surface mounted with rawbolts
- Please consider WiFi signal strength for this product

- Connects directly to your WiFi network using Bluetooth technology to support seamless pairing
- Polycarbonate construction is ideal for coastal applications
- Tunable between 2700K 6500K via WiZ app and voice control

GENERAL INFORMATION	
Wattage	11W
Lumens Delivered	840lm - 850lm (2700K - 6500K)
Lm/W	69lm/W - 77lm/W (2700K - 6500K)
Beam Angle	130
CRI	80
CCT	2700-6500K
Input	220-240V
Operating Temp	-10°C - 40°C
SDCM	6
Product Weight without Packaging	2.041 kg

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Floor	
Lumen Depreciation	L70 36,000h	
Warranty (Years)	3	
CE Mark	Yes	
Diameter	180 mm	
Height	1,000 mm	