



Leo

Leo CCT Bollard 450mm Code: ALEOLED/CCT/045/GR









PRODUCT FEATURES

- Modern styled bollard with polycarbonate construction suitable for residential and hospitality applications
- Polycarbonate construction is ideal for coastal applications
- CCT selectable between 3000K and 4000K
- Powered by Tridonic

GENERAL INFORMATION		
Wattage	8W	
Lumens Delivered	590lm (4000K)	
Lm/W	74lm/W (4000K)	
Beam Angle	130	
CRI	80	
ССТ	3000/4000K	
Input	220-240V	
Operating Temp	-10°C - 40°C	
SDCM	6	
Product Weight without Packaging	1.322 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Graphite	
IP Rating	IP65	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Floor	
Lumen Depreciation	L70 36,000h	
Warranty (Years)	3	
CE Mark	Yes	
Diameter	180 mm	
Height	450 mm	

Image: Construction of the second second

Category	Bollards
Application	Hospitality, Outdoor, Residential, Retail
Specification	Architectural

- White reflector with clear polycarbonate diffuser
- · Supplied c/w root mounting kit, can be surface mounted with rawbolts
- Non-dimmable

