



Leo



Part of the Bollards product category

Model	Leo CCT Bollard 1000mm
Code	ALEOLED/CCT/100/GR
Application	Hospitality, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	12W
Operating Temp	-10°C - 40°C
Lumens Delivered	940lm (4000K)
lm/W	76lm/W (4000K)
CCT	3000/4000K
Beam Angle	130

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without	2.01 kg
Packaging	
Colour / Finish	Graphite
Diameter	180 mm
Height	1,000 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Floor
Power Factor	0.85
L70 @ 25°C	L70 B50 36,000h

PRODUCT FEATURES

- Modern styled bollard with polycarbonate construction suitable for residential and hospitality applications
- White reflector with clear polycarbonate diffuser
- Polycarbonate construction is ideal for coastal applications
- Supplied c/w root mounting kit, can be surface mounted with rawbolts
- CCT selectable between 3000K and 4000K





Leo



Part of the Bollards product category



Model Leo CCT Bollard 1000mm
Code ALEOLED/CCT/100/GR
Application Hospitality, Outdoor, Residential, Retail

