





@ansell_lighting

Hospitality, Outdoor, Residential, Retail





Bollards

Architectural






Leo

Leo CCT Bollard 1000mm Code: ALEOLED/CCT/100/GR









- Modern styled bollard with polycarbonate construction suitable for residential and hospitality applications
- Polycarbonate construction is ideal for coastal applications
- CCT selectable between 3000K and 4000K
- · Powered by Tridonic

• White reflector with clear polycarbonate diffuser

Category

Application

Specification

- Supplied c/w root mounting kit, can be surface mounted with rawbolts
- Non-dimmable

GENERAL INFORMATION		
Wattage	12W	
Lumens Delivered	940lm (4000K)	
Lm/W	76lm/W (4000K)	
Beam Angle	130	
CRI	80	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	-10°C - 40°C	
SDCM	6	
Product Weight without Packaging	2.041 kg	

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	Graphite
IP Rating	IP65
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Floor
Lumen Depreciation	L70 36,000h
Warranty (Years)	3
CE Mark	Yes
Diameter	180 mm
Height	1,000 mm

Belfast: +44 (0) 2890 773750