



Category	Wall Lights
Application	Hospitality, Outdoor, Residential, Retail
Specification	Architectural

Leo Half Lantern

Leo CCT Half Lantern PIR **Code:** ALEOLED/HL/PIR



PRODUCT FEATURES

- Modern styled half wall lantern with polycarbonate construction suitable for commercial
 and residential applications
- Polycarbonate construction is ideal for coastal applications
- CCT selectable between 3000K and 4000K

- White reflector with clear polycarbonate diffuser
- PIR option for convenience and security. Incorporates manual override option
- Non-dimmable

	GENERAL INFORMATION
Wattage	8W
Lumens Delivered	330lm (4000K)
Lm/W	41 lm/W (4000K)
Beam Angle	130
CRI	80
ССТ	3000/4000K
Input	220-240V
Operating Temp	-10°C - 40°C
SDCM	6
Product Weight without Packag	ging 0.47 kg

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Graphite		
IP Rating	IP65		
Class Protection	2		
Internal / External	External		
Surface / Recessed / Suspended	Wall		
Lumen Depreciation	L70 54,000h		
Warranty (Years)	3		
CE Mark	Yes		
Height	282 mm		











Category	Wall Lights
Application	Hospitality, Outdoor, Residential, Retail
Specification	Architectural

Leo Half Lantern

Leo CCT Half Lantern PIR Code: ALEOLED/HL/PIR







