

@ansell\_lighting



ansellighting



Ansell Lighting





ansell\_lighting

# Lota

Lota CCT Recessed Modular Switch Dim  
Code: ALOTLED/DD1/M3

|               |                                   |
|---------------|-----------------------------------|
| Category      | Commercial Panels                 |
| Application   | Commercial, Education, Healthcare |
| Specification | Performance                       |



- Recessed luminaire suitable for educational or commercial applications
- Selectable CCT between 3000K, 4000K and 6000K output
- TP(a) as Standard

- UGR<19 (unified glare rating) compliant luminaire ideal for most interior
- Powder coated steel construction

| GENERAL INFORMATION              |                 |
|----------------------------------|-----------------|
| Wattage                          | 31W             |
| Lumens Delivered                 | 3200lm (4000K)  |
| Lm/W                             | 110lm/W (4000K) |
| Beam Angle                       | 85              |
| CRI                              | 80              |
| CCT                              | 3000/4000/6500K |
| Input                            | 220-240V        |
| Operating Temp                   | 0°C - 40°C      |
| SDCM                             | 3               |
| UGR                              | 17              |
| Cut-Out Size                     | 575x575mm       |
| Product Weight without Packaging | 4.27 kg         |

| TECHNICAL INFORMATION          |             |
|--------------------------------|-------------|
| Light Source                   | LED         |
| Colour / Finish                | White       |
| IP Rating                      | IP20        |
| Class Protection               | 2           |
| Internal / External            | Internal    |
| Surface / Recessed / Suspended | Recessed    |
| Lumen Depreciation             | L80 54,000h |
| Warranty (Years)               | 5           |
| CE Mark                        | Yes         |
| Height                         | 80 mm       |

