





Lota

Lota CCT Recessed Modular DALI-Emergency Code: ALOTLED/DM3

| | |
|---------------|-----------------------------------|
| Category | Commercial Panels |
| Application | Commercial, Education, Healthcare |
| Specification | Performance |



PRODUCT FEATURES

- Recessed luminaire suitable for educational or commercial applications
- Selectable CCT between 3000K, 4000K and 6000K output
- TP(a) as Standard
- UGR<19 (unified glare rating) compliant luminaire ideal for most interior
- Powder coated steel construction

| GENERAL INFORMATION | |
|----------------------------------|-----------------|
| Wattage | 31W |
| Lumens Delivered | 3200lm (4000K) |
| Lm/W | 110lm/W (4000K) |
| Beam Angle | 85 |
| CRI | 80 |
| CCT | 3000/4000/6500K |
| Input | 220/240V |
| Operating Temp | 0°C - 40°C |
| SDCM | 6 |
| UGR | 17 |
| Cut-Out Size | 575x575mm |
| Product Weight without Packaging | 0.01 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP20 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L80 54,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Height | 80 mm |

