



## Alto Graphite



- Surface bi-directional die-cast wall light providing adjustable beam angle suitable for residential and hospitality applications
- Independent beam angle adjustment between up and down distribution
- Minimum beam angle 0°, maximum beam angle 90°
- Die-cast aluminium body with graphite powder coated anodized paint finish for enhanced durability
- Non-dimmable

### Features

Feature 1	Surface bi-directional die-cast wall light providing adjustable beam angle suitable for residential and hospitality applications
Feature 2	Independent beam angle adjustment between up and down distribution
Feature 3	Minimum beam angle 0°, maximum beam angle 90°
Feature 4	Die-cast aluminium body with graphite powder coated anodized paint finish for enhanced durability
Feature 5	Non-dimmable

### General Information

Lamp Type	LED
IP Rating	IP54



IK Rating	IK05
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Wall
Warranty (Years)	3
Material	Aluminium
Technical Information	
Wattage	6W
Lumens Delivered	320lm
Lm/W	56lm/W
Beam Angle	90
CRI	80
CCT	4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C - 50°C
Lumen Depreciation	L80 50,000h
Power Factor	0.9



