











Lucca

Lucca CCT Multi Wattage Corridor Function Self-Code: ALUCLED/B/CF/SM3





PRODUCT FEATURES

- IP66 rated die-cast aluminium wall light with opal polycarbonate diffuser suitable for education, commercial and industrial applications
- One product with integral switches for multi-wattage and selectable CCT options
- · Powered by Tridonic

- Tamper-proof stainless steel allen key screws
- Non-dimmable

| GENERAL INFORMATION | | |
|----------------------------------|-------------------------|--|
| Wattage | 18W - 27W | |
| Lumens Delivered | 1300lm - 1900lm (4000K) | |
| Lm/W | 69lm/W - 71lm/W (4000K) | |
| Beam Angle | 105/110 | |
| CRI | 80 | |
| ССТ | 3000/4000K | |
| Input | 220-240V | |
| Operating Temp | 0°C - 40°C | |
| SDCM | 5 | |
| Product Weight without Packaging | 2.33 kg | |
| | | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------|--|
| Light Source | LED | |
| Colour / Finish | Black | |
| IP Rating | IP66 | |
| Class Protection | 1 | |
| Internal / External | External | |
| Surface / Recessed / Suspended | Wall | |
| Lumen Depreciation | L70 60,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Diameter | 298 mm | |

