


Lucca

Lucca CCT Multi Wattage Corridor Function Code: ALUCLED/B/CF

	Se	N G
@ansell_lighting	f	anselllighting
in Ansell Lighting	0	ansell_lighting

Category	Bulkheads	
Application	Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Industrial, Outdoor, Retail	
Specification	Performance	



PRODUCT FEATURES

- IP66 rated die-cast aluminium wall light with opal polycarbonate diffuser suitable for education, commercial and industrial applications
- One product with integral switches for multi-wattage and selectable CCT options
- · Powered by Tridonic

- Tamper-proof stainless steel allen key screws
 - Non-dimmable

GENERAL INFORMATION		
Wattage	27W	
Lumens Delivered	1300lm - 1900lm (4000K)	
Lm/W	69lm/W - 71lm/W (4000K)	
Beam Angle	105/110	
CRI	80	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	-20°C - 40°C	
SDCM	5	
Product Weight without Packaging	2.33 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP66	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Wall	
Lumen Depreciation	L70 60,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	298 mm	