





# Lynx

|                      |   |
|----------------------|---|
| <b>Application</b>   | Commercial, Healthcare, Industrial, Outdoor, Retail |
| <b>Specification</b> | Performance   |

## Lynx Wallpack 1-10V Emergency Code: ALWP/1/DD4/M3



### PRODUCT FEATURES

- Robust wall mounted luminaire for general accent illumination and suitable for education, commercial, industrial applications
- Power and CCT selectable; offering a choice of 2 outputs and 2 colour temperature options, in one luminaire
- Tamper-proof allen key screws supplied as standard
- Photocell and sensor options
- Integral emergency option provides downward illumination with a beam angle of 60°
- Die-cast aluminium body with vandal resistant polycarbonate Fresnel lens diffuser
- Multiple conduit entry and BESA box fixing points

| GENERAL INFORMATION |                         |
|---------------------|-------------------------|
| Wattage             | 18W-30W                 |
| Lumens Delivered    | 1400lm - 2200lm (4000K) |
| Lm/W                | 75lm/W (4000K)          |
| Beam Angle          | 70                      |
| CRI                 | 80                      |
| CCT                 | 3000/4000K              |
| Input               | 220/240V                |
| Operating Temp      | 5°C to 40°C             |

| TECHNICAL INFORMATION          |          |
|--------------------------------|----------|
| Light Source                   | LED      |
| Colour / Finish                | Black    |
| IP Rating                      | IP65     |
| Class Protection               | 1        |
| Internal / External            | External |
| Surface / Recessed / Suspended | Wall     |
| Warranty (Years)               | 5        |
| CE Mark                        | Yes      |

