





Lynx

| | |
|----------------------|---|
| Application | Commercial, Healthcare, Industrial, Outdoor, Retail |
| Specification | Performance |

Lynx Wallpack Microwave Sensor Emergency Code: ALWP/1/MWS/M3



PRODUCT FEATURES

- Robust wall mounted luminaire for general accent illumination and suitable for education, commercial, industrial applications
- Power and CCT selectable; offering a choice of 2 outputs and 2 colour temperature options, in one luminaire
- Tamper-proof allen key screws supplied as standard
- Photocell and sensor options
- Integral emergency option provides downward illumination with a beam angle of 60°
- Die-cast aluminium body with vandal resistant polycarbonate Fresnel lens diffuser
- Multiple conduit entry and BESA box fixing points

| GENERAL INFORMATION | |
|----------------------------------|-------------------------|
| Wattage | 18W-30W |
| Lumens Delivered | 1400lm - 2200lm (4000K) |
| Lm/W | 75lm/W (4000K) |
| Beam Angle | 70 |
| CRI | 80 |
| CCT | 3000/4000K |
| Input | 220/240V |
| Operating Temp | 5°C to 40°C |
| Product Weight without Packaging | 2.791 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|----------|
| Light Source | LED |
| Colour / Finish | Black |
| IP Rating | IP65 |
| Class Protection | 1 |
| Internal / External | External |
| Surface / Recessed / Suspended | Wall |
| Warranty (Years) | 5 |
| CE Mark | Yes |

