












## Lynx


## Application Commercial, Healthcare, Industrial, Outdoor, Retail Specification Performance

## Lynx Wallpack OCTO Smart Control Code: ALWP/1/OCTO









- Robust wall mounted luminaire for general accent illumination and suitable for education, commercial, industrial applications
- Power and CCT selectable; offering a choice of 2 outputs and 2 colour temperature options, in one luminaire
- Tamper-proof allen key screws supplied as standard
- Photocell and sensor options

- Integral emergency option provides downward illumination with a beam angle of  $60^{\circ}$
- Die-cast aluminium body with vandal resistant polycarbonate Fresnel lens diffuser
- Multiple conduit entry and BESA box fixing points

GENERAL INFORMATION		
Wattage	30W	
Lumens Delivered	1400lm - 2200lm (4000K)	
Lm/W	75lm/W (4000K)	
Beam Angle	70	
CRI	80	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	-10°C to 40°C	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Wall	
Warranty (Years)	5	
CE Mark	Yes	