Lynx

Part of the Bulkheads product category

Model	Lynx Wallpack Photocell
Code	ALWP/1/PC
Application	Commercial, Healthcare, Industrial, Outdoor, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	17.5W-26.5W
Operating Temp	-10°C to 40°C
Lumens Delivered	1400lm - 2200lm (4000K)
lm/W	75lm/W (4000K)
CCT	3000/4000K
Beam Angle	70

MATERIAL INFORMATION

Main Material	Aluminium, Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	2.741 kg
Colour / Finish	Black

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Wall
Power Factor	0.85
L70 @ 25°C	L70 B50 54000h

PRODUCT FEATURES

- Robust wall mounted luminaire for general accent illumination and suitable for education, commercial, industrial applications
- Integral emergency option provides downward illumination with a beam angle of 60°
- Power and CCT selectable; offering a choice of 2 outputs and 2 colour temperature options, in one luminaire
- Die-cast aluminium body with vandal resistant polycarbonate Fresnel lens diffuser
- Tamper-proof allen key screws supplied as standard





Lynx

5YR IP65 IK08 ON-SITE WARRANTY 2 YEARS

Part of the Bulkheads product category

Model	Lynx Wallpack Photocell
Code	ALWP/1/PC
Application	Commercial, Healthcare, Industrial, Outdoor, Retail





