

## Lynx

Lynx Wallpack Emergency Photocell Black Code: ALWPLED/M3/PC







Category

Application

Specification



Commercial, Education, Healthcare, Hospitality,

Industrial, Outdoor, Residential, Retail

f ansellighting

ansell\_lighting

@ansell\_lighting

in Ansell Lighting

Bulkheads

Performance

## **PRODUCT FEATURES**

- Robust wall mounted luminaire for general accent illumination and suitable for education, commercial, industrial applications
- Die-cast aluminium body with vandal resistant polycarbonate Fresnel lens diffuser
- Multiple conduit entry and BESA box fixing points

- Integral emergency option provides downward illumination with a beam angle of  $60^\circ$
- Tamper-proof allen key screws supplied as standard
- Photocell and sensor options

GENERAL INFORMATION		
Wattage	29W	
Lumens Delivered	2000lm	
Lm/W	711m/W	
Beam Angle	25/75	
CRI	80	
CCT	4000K	
Input	220-240V	
Operating Temp	0°C - 25°C	
SDCM	6	
Product Weight without Packa	ging 2.175 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Wall	
Lumen Depreciation	L70 60,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	300 mm	

