Lynx

Part of the Bulkheads product category

Model	Lynx Wallpack Emergency Black
Code	ALWPLED/M3
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	29W
Operating Temp	0°C - 25°C
Lumens Delivered	2000lm
lm/W	71lm/W
CCT	4000K
Beam Angle	25/75

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without Packaging	2.152 kg
Colour / Finish	Black
Height	300 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Wall
Power Factor	0.9
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- Robust wall mounted luminaire for general accent illumination and suitable for education, commercial, industrial applications
- Integral emergency option provides downward illumination with a beam angle of 60°
- Die-cast aluminium body with vandal resistant polycarbonate Fresnel lens diffuser
- Tamper-proof allen key screws supplied as standard
- Multiple conduit entry and BESA box fixing points





Lynx

Part of the Bulkheads product category

Model	Lynx Wallpack Emergency Black
Code	ALWPLED/M3
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Residential, Retail





