



# Lynx



Part of the Bulkheads product category

<b>Model</b>	Lynx Wallpack Emergency Black
<b>Code</b>	ALWPLED/M3
<b>Application</b>	Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Residential, Retail

### GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	29W
<b>Operating Temp</b>	0°C - 25°C
<b>Lumens Delivered</b>	2000lm
<b>lm/W</b>	71lm/W
<b>CCT</b>	4000K
<b>Beam Angle</b>	25/75

### MATERIAL INFORMATION

<b>Diffuser Material</b>	Polycarbonate
<b>Product Weight without Packaging</b>	2.152 kg
<b>Colour / Finish</b>	Black
<b>Height</b>	300 mm

### TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	3
<b>CRI</b>	80
<b>Internal / External</b>	External
<b>Surface / Recessed / Suspended</b>	Wall
<b>Power Factor</b>	0.9
<b>L70 @ 25°C</b>	L70 B50 60,000h

### PRODUCT FEATURES

- Robust wall mounted luminaire for general accent illumination and suitable for education, commercial, industrial applications
- Integral emergency option provides downward illumination with a beam angle of 60°
- Die-cast aluminium body with vandal resistant polycarbonate Fresnel lens diffuser
- Tamper-proof allen key screws supplied as standard
- Multiple conduit entry and BESA box fixing points





# Lynx



Part of the Bulkheads product category



**Model** Lynx Wallpack Emergency Black  
**Code** ALWPLED/M3  
**Application** Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Residential, Retail

