





Matrix

Application Hospitality, Residential, Retail

Specification Performance

Matrix 3 Linklight Code: AMALL3/1



PRODUCT FEATURES

- CCT Selectable LED linklight with integral driver suitable for residential and retail applications
- Moulded spine fitted with integral switch and fixed diffuser
- Supplied with 230V 1.5m mains power lead and linking plug adaptor
- Linkable up to a maximum of twelve fittings
- Side mounted switch allows installer the choice of 3000K or 4000K colour temperature options
- c/w angled and straight fixing clips
- End-to-end linking provides aesthetically pleasing seamless light output
- Non-dimmable

GENERAL INFORMATION

| | |
|----------------------------------|---------------|
| Wattage | 8W |
| Lumens Delivered | 800lm (4000K) |
| Lm/W | 100lm/W |
| Beam Angle | 100/160 |
| CRI | 80 |
| CCT | 3000/4000K |
| Input | 220/240V |
| Operating Temp | -10°C - 40°C |
| SDCM | 6 |
| UGR | 22 |
| Product Weight without Packaging | 0.188 kg |

TECHNICAL INFORMATION

| | |
|--------------------------------|---------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP20 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Ceiling, Wall |
| Lumen Depreciation | L80 60,000h |
| Warranty (Years) | 4 |
| CE Mark | Yes |
| Height | 37 mm |

