



Marlo



Part of the Commercial Linear product category



Model Marlo Bi-directional Linear UGR<19 1200mm Cool White
Code AMARLED4/CW
Application Ancillary, Commercial, Education, Healthcare, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	38W
Operating Temp	0°C - 25°C
Lumens Delivered	3700lm
lm/W	98lm/W
CCT	4000K
UGR	16
Beam Angle	90

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without	3.36 kg
Packaging	
Colour / Finish	Black
Height	80 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	90
Internal / External	Internal
Surface / Recessed / Suspended	Suspended
Power Factor	0.907
L70 @ 25°C	L70 B50 36,000h

PRODUCT FEATURES

- Mattone Bricklight CCT Surface Mounted Box
- Supplied bidirectional light output as standard (directional only option can be selected if required)
- High output, high efficiency 90° lens technology offers optimum glare control and comfort for task / office applications.
- Pre-wired with 2 metre cable
- Adjustable suspension points c/w suspension kit





Marlo



Part of the Commercial Linear product category



- Model** Marlo Bi-directional Linear UGR<19 1200mm Cool White
- Code** AMARLED4/CW
- Application** Ancillary, Commercial, Education, Healthcare, Retail

