



# Matala



Part of the Wall Lights product category

<b>Model</b>	Matala
<b>Code</b>	AMATROLED
<b>Application</b>	Hospitality, Outdoor, Residential, Retail

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	8
<b>Operating Temp</b>	-20°C - 25°C
<b>Lumens Delivered</b>	260lm (4000K)
<b>lm/W</b>	37lm/W (4000K)
<b>CCT</b>	3000K/4000K

## MATERIAL INFORMATION

<b>Main Material</b>	Aluminium
<b>Product Weight without</b>	0.734 kg
<b>Packaging</b>	
<b>Colour / Finish</b>	Graphite
<b>Diameter</b>	195 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	3
<b>CRI</b>	80
<b>Internal / External</b>	External
<b>Surface / Recessed / Suspended</b>	Wall
<b>Power Factor</b>	0.99

## PRODUCT FEATURES

- Surface mounting ultra-slim low level circular pathway light with downward light-spill suitable for residential and hospitality applications
- Die-cast aluminium construction with graphite paint finish
- Screwless front cover with concealed allen key access provides security
- Selectable CCT between 3000K and 4000K
- Pre-wired with 1 metre of rubber insulated cable for ease of installation





# Matala



Part of the Wall Lights product category

<b>Model</b>	Matala
<b>Code</b>	AMATROLED
<b>Application</b>	Hospitality, Outdoor, Residential, Retail

